

# OPTOTRONIC® LED Power Supply

## OT100W/347-480/1250C/2DIMLT2/P6-Technical Specifications



### ELECTRICAL SPECIFICATIONS

#### Input

Input Voltage (VAC)	347-480V (+/- 10%)	
Frequency Range (Hz)	50 – 60 Hz (+/- 10%)	
	<b>347V</b>	<b>480V</b>
Input Current (A)	0.34	0.25
THD @ Full load	<10%	<10%
Power Factor @ Full load	>0.95	>0.95
Efficiency @ Full load	≥86%	≥90%
Inrush Current (A <sub>pk</sub> )	41.5A, 155μs	63A, 155μs

#### Output

Output Current (mA)	600-1250mA 1mA resolution (programmable)
Output Voltage (VDC)	30-100VDC
Output Ripple Current	<25% @ 1250mA
Max. Output power (W)	100W
LED Power-up time	< 1 sec
Load Regulation	<5%
Line Regulation	<5%
Over voltage protection	Yes
Over load protection	Current foldback @105W
Output short-circuit protection	Yes

#### Dimming

Dimming Control	0 – 10V (Isolated)* AstroDIM
Dimming Range	10-100%
Dimming Type	Analog
Source/Sink Current	1mA

\* Class 2 or non-Class 2 wiring allowed

### GENERAL INFORMATION

Item Number	79207
Type	Constant Current
Output Power	100W (Max.)
Programming tool	51645; <a href="#">Software</a>
Programmable features	Output current Dimming level LED thermal protection AstroDIM LEDSet Gen2 Constant Lumen output End of life indicator

### ELECTRICAL SPECIFICATIONS

#### LED thermal protection (NTC)

NTC value active range	≤ 25kΩ
Output level minimum	User defined

### ENVIRONMENTAL SPECIFICATIONS


Ambient Operating Temperature	-40 °C to 55 °C
Case Temperature (T <sub>c</sub> )	85°C** 90°C (max)
Max. Storage Temp.	70°C
Max. Relative Humidity (%)	95% non condensing
Transient Protection	ANSI C62.41 Cat.B 6.0kV *
IP Rating	IP66
UL Environmental Rating	Damp & Wet
UL File number	E320395
EMI Compliance	FCC Part 15 Class A
Sound Rating	Class A

\*\* Warranty applicable only at 85°C

\*-Meets only 4kV for common mode combination wave




## WIRING DIAGRAM



**Note 1:** Maximum suggested remote mounting distance is 16 feet. For additional information on further distances and EMI compliance reference application note LED126.

**Note 2:** The Dimming input is isolated and will allow Class 2 or non-Class 2 wiring across Purple and Gray wires


## MECHANICAL DIAGRAM




### MECHANICAL DIAGRAM

Length	6.61" (168mm)
Width	2.36" (60mm)
Height	1.5" (38.1mm)
Mounting length	6.0" (152.4mm)
Mounting slot width	0.28" (7mm)

## OPERATING RANGE




## DIMMING CURVE






*\*The absolute minimum current the driver can deliver is 60mA*

Efficiency @ 347V




Efficiency @ 480V




**Power Factor vs Output Power****Power Factor vs Input Voltage**

### THD vs Output Power




### THD vs Input Voltage



## LED THERMAL PROTECTION (NTC) CHARACTERISTIC


The LED thermal protection feature of the OT100W helps reduce the temperature of the LED module by reducing the output current in case of abnormal temperature conditions. To use this feature a third party NTC thermistor should be connected to the LED power supply as shown in the wiring diagram below.



In the end application, care must be taken to place the NTC thermistor close to the hottest spot on the LED module. If LED thermal protection is not required the NTC port on the LED power supply connector can be left open. Vishay, EPCOS, Murata, Panasonic are some of the manufacturers of NTC thermistor. EPCOS part number for reference only **B57164K153J (15k $\Omega$  @ 25°C)**. Murata part number for reference only - **NCP03XH223J05RL (22k $\Omega$  @ 25°C)**

**Note 2:** Graphs for reference. The de-rating limits can be programmed using the OT Programmer

**Derating start = 6.3k $\Omega$ ; Derating end = 4.3k $\Omega$ ; Min output level = 10%**



## AstroDIM

AstroDIM is an autonomous five level (1 Power ON & 4 Dimming levels) dimming protocol. It provides multi-stage night-time power reduction based on an internal timer; there is no need for an external control infrastructure. The ECG is automatically aligned to the on and off times for the street lighting and provide a defined output for the particular period of time. Compared with conventional systems there are significant cost savings. AstroDIM is designed for dimming without any external control wiring. Therefore, AstroDIM helps to save energy, extend the life of the driver and the LED module and reduce light pollution, even if only a power line is available. In AstroDIM operation, the driver executes a preset dimming profile, which can be reconfigured via the OT Programming Tool. The autonomous dimming is regulated by an integrated timer (no real-time clock), which adjusts the dimming profile according to the previous night (operation from switch-on to switch-off).

## LEDset 2

LEDset (Gen2) is an analog interface, allowing basic communication between a LED control gear and one or more LED modules. It allows setting the output current of the LED driver by providing a highly accurate voltage reference (Vset) to the driver. The interface supports the following functions:

- Output current setting of the constant current LED control gear to single LED modules as well as to series/parallel connected LED modules
- Best matching of LED control gear and modules working point
- Self-configuration according to system structure, automatic tracking of technology development
- Easy mode of operation
- Additional monitoring & protection features (e.g. thermal protection of the LED modules)

Therefore, the typical applications of this interface are single or multiple LED module parallel connections, offering an increasing choice of modular capabilities and low cost thermal protections circuits.

For detailed information on LEDset interface please refer to *Technical Application guide LEDset interface* (LED 409)

**Note 3:** When the LEDset feature is enabled, the LED Thermal protection (NTC) feature is disabled.

## CONSTANT LUMEN MAINTENANCE

The Constant Lumen Maintenance feature of the OT100W helps to maintain the required lumen output of the fixture at a constant level throughout its lifetime. In general LED's lumen output will depreciate over time and in order to maintain sufficient light level towards the end of lifetime, the LED's are driven at high current initially and will result in more energy consumption. The constant lumen maintenance will give the flexibility to drive the LEDs at optimal driving current throughout its lifetime. This helps in energy savings, constant light output and enhanced reliability of the system.


**Note 4:** A detailed step-by-step instructions are outlined in the '[OT Programmer User Manual V2.1](#)'

## END OF LIFE INDICATOR

The End-of-Life indicator feature helps the end user to receive a signal from the fixture indicating that it has reached its programmed life-time. After the LED driver reaches the programmed life-time, whenever it is turned ON, it stays at 'Dim' level (10%) for 10 minutes and reaches its appropriate level.



## LIFETIME VS CASE TEMPERATURE



## INRUSH CHARACTERISTICS

Vin (V)	Ipeak (A)	T (@ 50% of Ipeak)
347	41.5	155 μs
480	63	155 μs

## DIMMER COMPATIBILITY

Manufacturer	Part no
Encelium EMS	EN-LCM-1R10V-GB2-BK EN-LCM-1R10V-GB2-BK/DR EN-ALC-1R10V-GB2-BK EN-ALC-1R10V-GB2-BK-DR
SYLVANIA	ELMC-SL3W-TVWBX/UNV
Leviton	IP710-DLX
Lutron	DVTV-XX
Wattstopper	ADF-120277
Synergy lighting Controls	ISD BC

**Note 5:** The absence of a dimmer from this chart does not necessarily imply incompatibility. Please reference the dimmer manufacturer's instructions for installation.

## UL CONDITIONS OF ACCEPTABILITY (E320395)

Conditions of Acceptability – When installed in the end-product, consideration shall be given to the following:

- Rated output loading for these products was achieved using electronic loads and/or actual LED Loads.
- The temperature tests were performed at nominal 40°C ambient for TL Type reference temperatures. These models were also tested at elevated ambient temperatures and the Tc applied for non-TL applications for these models is 90°C.

Non-TL Type application:

Model No.	Test ambient temperature	Tc rating at elevated temp.
OT100W/347-480/1250C/2DIMLT2/P6	61	90°C
OT100W/347-480/800C/2DIMLT2/P6	61	90°C

- As part of temperature testing, the case temperature at Tc was monitored. During the normal temperature test of the end product, the temperature at Tc is to be monitored. The absolute value at Tc cannot exceed the specified Tref, noted in product characteristics table for a TL application.
- These products are intended for building in. Acceptability of the LED driver- with respect to environmental, mounting, spacing, casualty, temperature and segregation- is to be determined as part of the end device evaluation.
- These products are provided with 18 AWG, leads, refer to descriptive pages for input and output connections. Acceptability of the leads relative to strain relief and secureness, is to be determined as part of the end device evaluation.
- These products are dimmable using a low voltage 0-10 V or a DALI proprietary interface. This interface is a sink, since the interface circuit operates from an external source of supply. The interface circuit has been evaluated for isolation from primary (input) and secondary (output) circuits with spacings based on the maximum rated branch supply, 277 Vac. A Dielectric test was applied to verify spacing in the dimming circuit, at 2500Vac.
- The PWB spacings for use in wet locations have been evaluated to UL8750 spacing requirements. The driver is completely potted and spacing requirements comply with Table 7.4 in UL8750, Parts Potted or subsequently coated.
- These drivers are Type TL rated and shall be marked with a TC point on the label for temperatures recorded during temperature testing performed in a 40°C ambient.

Model No.	Tc point on label, °C
OT100W/347-480/XXXC/2DIMLT2/P6 (XXXC- 800mA max)	86/62
OT100W/347-480/YYYYC/2DIMLT2/P6 (YYYY=1250mA max)	90/71

- These Drivers are 100% potted refer to ILL. 14 for assembly drawings demonstrating amount of potting applied.

## WARRANTY

OPTOTRONIC® products are covered by our LED Module, OPTOTRONIC Power Supply or Control Warranty. For additional details, refer to the latest version of the warranty (LED089) available at [www.osram-americas.com/optotronic](http://www.osram-americas.com/optotronic)

OSRAM LEDset and OPTOTRONIC are registered trademarks of OSRAM GmbH..  
Specifications subject to change without notice

© 2015 OSRAM SYLVANIA Inc. 09/15

© 2015 OSRAM SYLVANIA Inc. 02/14